PERFORMANCE		
FRESH FROZEN INPUT	10 - 40 kg	
DRY INPUT	3 - 12 kg	
8 HOUR MAX FRESH FROZEN THROUGHPUT CAPACITY	160 kg	
8 HOUR MAX DRY THROUGHPUT CAPACITY	48 kg	
REQUIRED OPERATORS	1	
AGITATION CAPACITY PER KG INPUT (FRESH FROZEN)	7.5 L/kg	
WATER CONSUMPTION PER RUN	350 L	

SYSTEM SPECIFICATIONS	
POWER REQUIREMENTS	230 V / 1 Ph / 60 Hz
NOMINAL INPUT CURRENT	26 A
LINE FUSE	30 A
UNIT WEIGHT EMPTY	500 kg (1102 lbs)
UNIT WEIGHT FULL	900 kg (1985 lbs)
MINIMUM DOORWAY SIZE	34"

TECHNICAL SPECIFICATIONS	
FALSE BOTTOM SCREEN SIZE	220 micron
COMPONENT IP RATING	IP55 - IP69K
WETTED COMPONENTS MATERIAL SPECIFICATIONS	316 SS 32 Ra
NON-WETTED COMPONENT SPECIFICATIONS	304 SS
TANK AND SINK INSULATION	1" AP ARMAFLEX
DIMPLE JACKET COOLING SYSTEM	OPTIONAL

INCLUSIONS
STAINLESS STEEL MOTORS AND SANITARY PUMP
PHARMA GRADE TEMPERATURE PROBE
1 X REPLACEMENT SEPARATOR SCREEN
2 X 32 GAL LAB SERIES 3/4 MESH BUBBLE BAGS
SYSTEM TOOL AND SPARE PARTS BOX
VARIABLE FREQUENCY CONTROL FOR ALL DRIVES
TOUCH SCREEN OPERATION
COMPREHENSIVE TECHNICAL SUPPORT PACKAGE
3D LAB LAYOUT DESIGN
AUXILIARIY SELECTION AND SIZING
VIRTUAL COMMISSIONING AND TRAINING

WT-CRAFT+ 300L EXTRACTION SYSTEM **CUT SHEET** Whistler Technologies products are warrantied against defects for twelve months.


⊕ [] SCALE UNO: NTS

B

1/1

201 - 1420 ALPHA LAKE ROAD WHISTLER, BC CANADA V8E 0R8 TEL: +1 604 962 1420 whistlertechnologies.ca

WHISTLER
TECHNOLOGIES
CORPORATION



Enquire about our 6* service program

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF WHISTLER TECHNOLOGIES CORPORATION, ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITED PERMISSION OF WHISTLER TECHNOLOGIES CORPORATION IS PROHIBITED.

